

# VISUAL OIL ANALYSIS:

## Oil Level Indicator

Monitor the oil level in your machine machinery.



### APPLICATIONS:

- Pumps
- Gearboxes
- Storage Tanks



# Specifications

## Material:

- Stain-resistant acrylic

## Recommended Temperature Range:

- -40 °F to 200 °F
- -40 °C to 93 °C

## Maximum Operating Pressure:

- 65 psi
- 4.48 bar

## Chemical Compatibility:

- All gear, mineral and synthetic oils

## Available Options:

- Lengths ranging from 3" to 15"
- Stainless steel fittings
- Des-Case ND-2 Breather 0.3 $\mu$  absolute ( $\beta_{0.3} \geq 1000$ ) (15" and larger models)
- Custom lengths available upon request

## Sizing:

Part Number	Description	Overall Length		Diameter of Acrylic	
		(in)	(cm)	(in)	(cm)
DC-OLI3	3" OLI - 1/2" MNPT X 1/2" MNPT	3	7.62	0.875	2.223
DC-OLI6	6" OLI - 1/2" MNPT X 1/2" MNPT	6	15.24	0.875	2.223
DC-OLI9	9" OLI - 1/2" MNPT X 1/2" MNPT	9	22.86	0.875	2.223
DC-OLI12	12" OLI - 1/2" MNPT X 1/2" MNPT	12	30.48	0.875	2.223
DC-OLI15	15" OLI - 1/2" MNPT X 1/2" MNPT	15	38.10	0.875	2.223